



DLM/A (Dry Lock Micro Type A) Port System Charts

PORT OPTIONS

Some lenses have more than one port option. The first column is always the recommended option for the best compromise of imaging quality, performance, and handling with any given lens.

PRODUCT(S) REQUIRED

Where multiple lines of products are listed for a given option, all products listed are required to make a complete compatible lens port.

LENSES REFERENCING “+4 DIOPTRER REQUIRED”

A +4 diopter is available for purchase through your local camera store, and is commonly sold in a set with +1 and +2 close-up lenses. Common brands include Tiffen and Hoya. Make sure to purchase the correct size for your lens. The thread diameter is usually referenced on the front of the lens in millimeters (\emptyset 58mm, 67mm, etc.). All photos will be out of focus if a +4 diopter is required but not used.

Canon EF-M Lenses

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
<p>8 mm Rokinon f/3.5 Aspherical Fisheye + Canon EF-EOS M Mount Adapter 6098B002WB</p> <p><i>Tripod foot must be removed from the mount adapter.</i></p>	<p>Auto focus not supported by this lens. Preset focus to 14".</p> <p>Product(s) required:</p> <p>5510.45 Dome 5516.65 Extension 5516.80 Adapter</p>		
<p>8-15 mm Canon EF f/4L Fisheye USM + Canon EF-EOS M Mount Adapter 6098B002WB</p> <p><i>Tripod foot must be removed from the mount adapter</i></p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required:</p> <p>5510.45 Dome 5516.65 Extension 5516.80 Adapter</p>		
<p>10-17 mm Tokina AT-X f/3.5-4.5 DX Fisheye + Canon EF-EOS M Mount Adapter 6098B002WB</p> <p><i>Tripod foot must be removed from the mount adapter.</i></p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required:</p> <p>5510.45 Dome 5516.65 Extension 5516.80 Adapter</p>		
<p>10-18 mm Canon EF-S f/4.5-5.6 IS STM + Canon EF-EOS M Mount Adapter 6098B002WB</p> <p><i>Tripod foot must be removed from the mount adapter.</i></p>	<p>The only port option that supports zoom. AF only.</p> <p>Product(s) required:</p> <p>5516.15 Dome Port 5516.65 Extension 5515.06 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required:</p> <p>5510.45 Dome 5516.65 Extension 5516.80 Adapter</p>	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
11-22 mm Canon EF-M f/4-5.6 IS STM	<p>The only port option that supports zoom. AF only.</p> <p>Product(s) required: 5516.15 Dome Port 5515.03 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.80 Adapter</p>	
15 mm Sigma f/2.8 EX DG Diagonal Fisheye + Canon EF-EOS M Mount Adapter 6098B002WB <i>Tripod foot must be removed from the mount adapter.</i>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Shade should be removed to reduce vignetting. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.65 Extension 5516.80 Adapter</p>	<p>Compact and lightweight for travel. AF only.</p> <p>Product(s) required: 5516.12 Dome Port 5516.65 Extension</p>	
15-45 mm Canon f/3.5-6.3 IS STM	<p>The only port option that supports zoom. AF only.</p> <p>Product(s) required: 5516.15 Dome Port 5515.03 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.80 Adapter</p>	<p>The magnifying effect of a flat port is good for macro photography. Very minimal vignetting (dark shadows in the corners of the image) is present at 15mm. Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5516.45 Flat Port</p>
16-35 mm Canon EF f/2.8L II USM + Canon EF-EOS M Mount Adapter 6098B002WB <i>Tripod foot must be removed from the mount adapter.</i>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome (2) 5516.65 Extensions 5516.80 Adapter</p>		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
18-55 mm Canon EF-M f/3.5-5.6 IS STM	<p>The only port option that supports zoom. AF only.</p> <p>Product(s) required: 5516.15 Dome Port 5509.30 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.80 Adapter</p>	
28 mm Canon EF-M f/3.5 Macro IS STM	<p>AF only.</p> <p>Product(s) required: 5516.45 Flat Port</p>		
40 mm Canon EF f/2.8 STM + Canon EF-EOS M Mount Adapter 6098B002WB <i>Tripod foot must be removed from the mount adapter.</i>	<p>The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only.</p> <p>Product(s) required: 5516.50 Flat Port</p>	<p>A dome port provides the full angle of coverage underwater. AF only.</p> <p>Product(s) required: 5516.11 Dome Port</p>	
60 mm Canon EF-S f/2.8 Macro USM + Canon EF-EOS M Mount Adapter 6098B002WB <i>Tripod foot must be removed from the mount adapter.</i>	<p>AF only.</p> <p>Product(s) required: 5516.50 Flat Port 5516.65 Extension</p>		
100 mm Canon EF-S f/2.8L Macro IS USM + Canon EF-EOS M Mount Adapter 6098B002WB <i>Tripod foot must be removed from the mount adapter.</i>	<p>AF only.</p> <p>Product(s) required: 5516.50 Flat Port 5516.65 Extension 5516.70 Extension</p>		

Olympus & Panasonic Micro 4/3 Lenses

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
7-14 mm f/2.8 Olympus ED PRO	<p>The only port option that supports zoom. AF only.</p> <p>Product(s) required: 5516.17 Dome Port 5509.20 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.67 Extension 5516.80 Adapter</p>	<p>The only port option that supports zoom. Minimal vignetting is present at 7mm. AF only.</p> <p>Product(s) required: 5516.15 Dome Port 5509.28 Zoom Gear</p>
7-14 mm f/4 Panasonic Lumix G Vario ASPH H-F007014	<p>The only port option that supports zoom. AF only.</p> <p>Product(s) required: 5516.16 Dome Port 5515.20 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.80 Adapter</p>	
8 mm f/1.8 Olympus M.Zuiko Fisheye Pro	<p>Larger radius dome is best for split shots (half-in, half-out of the water). No vignetting. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.80 Adapter</p>	<p>Slight vignetting (dark shadows around the edges of the image) will be present. AF only.</p> <p>Product(s) required: 5516.11 Dome Port 5516.65 Extension</p>	
8 mm f/3.5 Panasonic Lumix G Fisheye H-F008	<p>No vignetting. AF only.</p> <p>Product(s) required: 5516.11 Dome Port</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Dome shade must be removed. Slight vignetting (dark shadows in the corners of the image) will be present. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.80 Adapter</p>	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
8-18 mm f/2.8-4.0 Panasonic Leica DG Vario-Elmarit ASPH	The only port option that supports zoom. AF only. <u>Product(s) required:</u> 5516.17 Dome Port 5509.30 Zoom Gear	Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.65 Extension 5516.80 Adapter	
9-18 mm f/4.0-5.6 Olympus M.Zuiko ED	The only port option that supports zoom. AF only. <u>Product(s) required:</u> 5516.15 Dome Port 5516.65 Extension 5509.28 Zoom Gear	Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	
12 mm f/2 Olympus M.Zuiko Digital ED	Best for close focus wide angle and most compact for travel. AF only. <u>Product(s) required:</u> 5516.11 Dome Port	Larger radius dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	AF only. <u>Product(s) required:</u> 5516.15 Dome Port
12 mm f/1.4 Panasonic Lumix ASPH	Recommendation not available		
12-32 mm f/3.5-5.6 Panasonic Lumix G Vario HD H-FS12032K	The only port option that supports zoom. AF only. <u>Product(s) required:</u> 5516.15 Dome Port 5515.01 Zoom Gear	Allows the attachment of 67mm threaded wide angle or macro lenses. Lens must be used at 32mm to eliminate vignetting. Zoom not supported. Lens must be used at a fixed focal length. AF only. <u>Product(s) required:</u> 5516.45 Flat Port	Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
12-35 mm Panasonic f/2.8 ASPH Power OIS H-HS12035	<p>The only port option that supports zoom (or focus). Zoom gear may alternatively be used to manually focus.</p> <p>Product(s) required:</p> <p>5516.15 Dome Port 5516.65 Extension 5509.27 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required:</p> <p>5510.45 Dome 5516.65 Extension 5516.80 Adapter</p>	
12-40 mm f/2.8 Olympus M.Zuiko ED Pro	<p>Compared to a shorter port, this option puts the lens element closer to the center of the dome sphere for improved sharpness. AF only.</p> <p>Product(s) required:</p> <p>5516.16 Dome Port 5516.65 Extension 5509.28 Zoom Gear</p>	<p>AF only.</p> <p>Product(s) required:</p> <p>5516.15 Dome Port 5516.65 Extension 5509.28 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required:</p> <p>5510.45 Dome 5516.65 Extension 5516.80 Adapter</p>
12-50 mm f/3.5-6.3 Olympus M.Zuiko Digital ED EZ	<p>The only port option that supports zoom. Switch lens to "M-ZOOM" prior to installation. No access to L-Fn or Macro buttons. AF only.</p> <p>Product(s) required:</p> <p>5516.15 Dome Port 5515.02 Zoom Gear</p>	<p>The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. Lens must be used at 50mm to eliminate vignetting. Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required:</p> <p>5516.50 Flat Port 5516.65 Extension</p>	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
12-60 mm f/2.8-4.0 Panasonic Leica DG Vario-Elmarit ASPH Power OIS	<p>The only port option that supports zoom. AF only.</p> <p>Product(s) required:</p> <p>5516.15 Dome Port 5516.67 Extension 5509.27 Zoom Gear</p>	<p>The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. Lens must be used between 35-60mm to eliminate vignetting. Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required:</p> <p>5516.45 Flat Port 5516.70 Extension</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). No vignetting. Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required:</p> <p>5510.45 Dome 5516.80 Adapter 5516.65 Extension</p>
12-60 mm f/3.5-5.6 Panasonic ASPH Power OIS	<p>The only port option that supports zoom. Zoom gear may alternatively be used to manually focus.</p> <p>Product(s) required:</p> <p>5516.15 Dome Port 5516.65 Extension 5509.27 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required:</p> <p>5510.45 Dome 5516.65 Extension 5516.80 Adapter</p>	
12-100 mm f/4.0 Olympus M.Zuiko Digital ED IS Pro	<p>The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. Lens must be used between 65-100mm to eliminate vignetting. Zoom not supported. Lens must be used at a fixed focal length. No access to L-Fn button or IS switch. AF only.</p> <p>Product(s) required:</p> <p>5516.50 Flat Port 5516.65 Extension 5516.70 Extension</p>		
14 mm f/2.5 Panasonic ASPH II H-H014AK	<p>Recommendation not available</p>		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
14-42 mm f/3.5-5.6 Olympus M.Zuiko ED	<p>The only port option that supports zoom. Autofocus only.</p> <p>Product(s) required: 5516.15 Dome Port 5515.03 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.80 Adapter</p>	
14-42 mm f/3.5-5.6 Olympus M.Zuiko ED EZ	<p>The only port option that supports zoom. Autofocus only.</p> <p>Product(s) required: 5516.15 Dome Port 5515.04 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.80 Adapter</p>	
14-42 mm f/3.5-5.6 Olympus M.Zuiko ED II (R)	<p>The only port option that supports zoom. Autofocus only.</p> <p>Product(s) required: 5516.15 Dome Port 5515.01 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.80 Adapter</p>	
14-42 mm f/3.5-5.6 Olympus M.Zuiko ED II (R) + Olympus Fisheye Converter FCON-P01	<p>The only port option that supports zoom. Maximum telephoto is 37mm without making contact with the inside of the dome. AF only.</p> <p>Product(s) required: 5516.15 Dome Port 5516.65 Extension 5515.01 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.65 Extension 5516.80 Adapter</p>	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
14-42 mm f/3.5-5.6 Panasonic H-FS014042	Zoom gear not available. Lens must be used at a fixed focal length. AF only. <u>Product(s) required:</u> 5516.15 Dome Port		
14-42 mm f/3.5-5.6 II Panasonic ASPH Mega OIS H-FS1442A	The only port option that supports zoom. AF only. <u>Product(s) required:</u> 5516.15 Dome Port 5515.21 Zoom Gear	Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. Lens must be used between 21-42mm to eliminate vignetting. Zoom not supported. Lens must be used at a fixed focal length. AF only. <u>Product(s) required:</u> 5516.45 Flat Port
14-42 mm Panasonic f/3.5-5.6 ASPH POWER OIS H-PS14042S	Port recommendation not available for this lens.		
14-45 mm f/3.5-5.6 Panasonic ASPH Mega OIS H-FS014045	AF only. <u>Product(s) required:</u> 5516.15 Dome Port 5515.22 Zoom Gear		
14-140 mm Panasonic f/3.5-5.6 ASPH H-FS14140 14-140 mm Panasonic f/4.0-5.8 ASPH H-VS014140	Lens not recommended for underwater use due to extended zoom range.		
14-150 mm f/4.0-5.6 Olympus M.Zuiko ED II	Lens not recommended for underwater use due to extended zoom range.		
15 mm Panasonic f/1.7 ASPH H-X015 15 mm Panasonic f/1.7 ASPH H-X015K	Port recommendation not available for this lens.		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
17 mm Olympus f/1.8	AF only. <u>Product(s) required:</u> 5516.11 Dome Port	Larger radius dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	
19 mm Sigma f/2.8 EX DN	AF only. <u>Product(s) required:</u> 5516.11 Dome Port		
20 mm Panasonic f/1.7 II ASPH H-H020A	AF only. <u>Product(s) required:</u> 5516.11 Dome Port	Larger radius dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.45 Flat Port
25 mm Olympus f/1.8	AF only. <u>Product(s) required:</u> 5516.11 Dome Port	Larger radius dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.45 Flat Port
25 mm Panasonic f/1.4 ASPH H-X025	The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.45 Flat Port		
30 mm f/3.5 Olympus M.Zuiko Digital ED Macro	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.45 Flat Port	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.50 Flat Port	AF or MF. Manual focus requires optional focus gear. <u>Product(s) required:</u> 5516.15 Dome Port <u>Optional accessories:</u> 5515.02 Focus Gear

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
30 mm f/2.8 Panasonic Macro ASPH Mega OIS H-HS030	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.45 Flat Port		
40-150 mm f/4.0-5.6 Olympus M.Zuiko ED R	Lens not recommended for underwater use due to extended zoom range.		
45 mm Olympus f/1.8	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.45 Flat Port		
45 mm f/2.8 Panasonic ASPH Mega OIS H-ES045	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.45 Flat Port	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.50 Flat Port	
45-150 mm Panasonic H- FS45150K 45-175 mm Panasonic f/4.0-5.6 ASPH H-PS45175K 45-200 mm Panasonic f/4.0-5.6 H-FS045200	Lens not recommended for use underwater due to range.		
60 mm f/2.8 Olympus M.Zuiko Macro ED	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded and accepts 3.0" diameter filters. AF only. <u>Product(s) required:</u> 5516.45 Flat Port 5516.65 Extension	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.50 Flat Port 5516.65 Extension	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
75 mm f/1.8 Olympus M.Zuiko	Lens not recommended for underwater use due to minimum focus distance of 33.07" (0.84 m).		
75-300 mm f/4.8-6.7 Olympus M.Zuiko ED II	Lens not recommended for underwater use due to range and minimum focus distance of 35.43" (0.90 m).		
100-300 mm Panasonic f/4.0-5.6 H-FS100300	Lens not recommended for use underwater due to range.		

Sony E-Mount Lenses

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
<p>8-15 mm Canon f/4L EF Fisheye USM + Metabones EF to E Mount Adapter</p> <p><i>Tripod foot must be removed from Metabones adapter.</i></p>	<p>The only port option that supports zoom. Severe vignetting (shadows around the image) will be present at 8mm. AF only.</p> <p><u>Product(s) required:</u></p> <p>5516.15 Dome Port 5516.65 Extension 5509.28 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p><u>Product(s) required:</u></p> <p>5510.45 Dome 5516.69 Extension 5516.80 Adapter</p>	
<p>10-17 mm Tokina f/3.5-4.5 AT-X + Metabones EF to E Mount Adapter</p> <p><i>Tripod foot must be removed from Metabones adapter.</i></p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p><u>Product(s) required:</u></p> <p>5510.45 Dome 5516.65 Extension 5516.80 Adapter</p>	<p>Compact and lightweight for travel. Best for close focus wide angle. Zoom not supported. Lens must be used at a fixed focal length. Slight vignetting (shadows in the corners of the image) will be present at 10mm. AF only.</p> <p><u>Product(s) required:</u></p> <p>5516.12 Dome Port 5516.65 Extension</p>	
<p>10-18 mm Sony f/4 OSS E SEL1018</p>	<p>The only port option that supports zoom. AF only.</p> <p><u>Product(s) required:</u></p> <p>5516.15 Dome Port 5515.43 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p><u>Product(s) required:</u></p> <p>5510.45 Dome 5516.80 Adapter</p>	
<p>12 mm Rokinon f/2.8 Full Frame Fisheye + Metabones EF to E Mount Adapter</p> <p><i>Tripod foot must be removed from Metabones adapter.</i></p>	<p>Slight vignetting (shadows in the corners of the image) will be present.</p> <p><u>Product(s) required:</u></p> <p>5516.15 Dome Port 5516.65 Extension 5509.27 Focus Gear</p>		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
12 mm Sony f/2.8 Carl Zeiss Touit	Larger radius dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	Compact and lightweight for travel. AF only. <u>Product(s) required:</u> 5516.12 Dome Port	
16 mm Sigma f/1.4 DC DN	Larger dome is best for split shots (half-in, half-out of the water). Compared to shorter ports, this option puts the lens element closest to the center of the dome sphere for optimal sharpness. AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.67 Extension 5516.80 Adapter	Larger radius dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	Compact and lightweight for travel. AF only. <u>Product(s) required:</u> 5516.15 Dome Port 5516.65 Extension
16 mm Sony f/2.8 E SEL16F28 16 mm Sony f/2.8 E SEL16F28 + Ultra Wide Converter VCL-ECU1	Larger radius dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	Compact and lightweight for travel. AF only. <u>Product(s) required:</u> 5516.11 Dome Port	
16 mm Sony f/2.8 E SEL16F28 + Ultra Wide Converter VCL-ECU2	Port recommendation not available for this lens combination.		
16 mm Sony f/2.8 E SEL16F28 + Sony Fisheye Conversion Lens VCL-ECF1 16 mm Sony f/2.8 E SEL16F28 + Sony Fisheye Converter VCL-ECF2	Larger radius dome is best for split shots (half-in, half-out of the water). Minimal vignetting (shadows in the corner of the image) will be present. AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	Compact and lightweight for travel. AF only. <u>Product(s) required:</u> 5516.11 Dome Port	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
16-35 mm Sony FE f/4 ZA OSS Vario-Tessar T*	<p>Due to the diameter of this lens, the Lens Extension must be attached to the housing and camera body installed prior to attaching lens to the camera. AF only.</p> <p>Product(s) required: 5516.15 Dome Port 5516.65 Extension 5515.43 Zoom Gear*</p> <p><i>* Use clear sleeve only with 1/8" thick foam strips attached directly to the inside of the zoom sleeve.</i></p>		
16-35 mm Canon EF f/4L USM + Metabones EF to E Mount Adapter <i>Tripod foot must be removed from Metabones adapter.</i>	<p>Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5516.12 Dome Port 5516.65 Extension 5516.70 Extension</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.65 Extension 5516.70 Extension 5516.80 Adapter</p>	
16-50 mm Sony f/3.5-5.6 OSS E PZ SELP1650	<p>The only port option that supports zoom. AF only.</p> <p>Product(s) required: 5516.15 Dome Port 5515.41 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p>Product(s) required: 5510.45 Dome 5516.80 Adapter</p>	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
16-70 mm Sony f/4 ZA OSS Vario-Tessar T* E SEL1670Z	<p>The only port option that supports zoom. AF only.</p> <p><u>Product(s) required:</u> +2 Diopter Required 5516.15 Dome Port 5516.65 Extension 5509.29 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p><u>Product(s) required:</u> 5510.45 Dome 5516.65 Extension 5516.80 Adapter</p>	<p>The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. Lens must be used between 50-70mm to eliminate vignetting. Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p><u>Product(s) required:</u> 5516.45 Flat Port 5516.70 Extension</p>
18 mm Zeiss Batis f/2.8	<p>Lens too large in diameter to fit in port system.</p>		
18-55 mm Sony f/3.5-5.6 OSS E SEL1855	<p>The only port option that supports zoom. AF only.</p> <p><u>Product(s) required:</u> 5516.15 Dome Port 5515.42 Zoom Gear</p>	<p>Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only.</p> <p><u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter</p>	
18-55 mm Canon f/4.5-5.6 IS STM + Metabones EF to E Mount Adapter <i>Tripod foot must be removed from Metabones adapter.</i>	<p>AF only.</p> <p><u>Product(s) required:</u> 5516.15 Dome Port 5516.65 Extension 5509.19 Zoom Gear</p>		
18-105 mm Sony f/4 G OSS E PZ SELP18105G	<p>Port recommendation not available for this lens.</p>		
18-200 mm Sony f/3.5-6.3 OSS E SEL18200(LE)	<p>Lens not recommended for use underwater due to range.</p>		
20 mm Sony f/2.8 E SEL20F28	<p>AF only.</p> <p><u>Product(s) required:</u> 5516.11 Dome Port</p>		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
20 mm Sony f/2.8 E SEL20F28 + Fisheye Converter VCL-ECF2	Larger radius dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	Compact and lightweight for travel. Best for close focus wide angle. AF only. <u>Product(s) required:</u> 5516.12 Dome Port	Compact and lightweight for travel. Best for close focus wide angle. AF only. <u>Product(s) required:</u> 5516.11 Dome Port
24-70 mm Sony FE f/4 ZA OSS Carl Zeiss Vario Tessar T*	Due to the diameter of this lens, the Lens Extension must be attached to the housing and camera body installed prior to attaching lens to the camera. AF only. <u>Product(s) required:</u> 5516.15 Dome Port 5516.69 Extension 5509.28 Zoom Gear		
24-240 mm Sony f/3.5-6.3 OSS E SEL24240	Lens not recommended for use underwater due to range.		
28 mm Sony f/2 FE SEL28F20	AF or MF. Manual focus requires optional focus gear. <u>Product(s) required:</u> 5516.15 Dome Port <u>Optional accessories:</u> 5509.31 Focus Gear	Larger radius dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	Compact and lightweight for travel. AF only. <u>Product(s) required:</u> 5516.11 Dome Port
28 mm Sony f/2 FE + Ultra Wide Converter SEL075UWC	AF only. <u>Product(s) required:</u> 5516.12 Dome Port 5516.70 Extension	Larger radius dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	
28-70 mm Sony f/3.5-5.6 OSS FE SEL2870	The only port option that supports zoom. AF only. <u>Product(s) required:</u> 5516.15 Dome Port 5509.31 Zoom Gear	Larger radius dome is best for split shots (half-in, half-out of the water). Zoom not supported. Lens must be used at a fixed focal length. AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.80 Adapter	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
30 mm Sony E f/3.5 Macro E SEL30M35	The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.45 Flat Port		
35 mm Sony f/1.8 OSS E SEL35F18	Port recommendation not available for this lens.		
50 mm Sony f/1.8 OSS E SEL50F18 50 mm Sony f/1.8 FE	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.45 Flat Port	Manual focus with optional focus gear. <u>Product(s) required:</u> 5516.15 Dome Port <u>Optional accessories:</u> 5515.42 Focus Gear	AF only. <u>Product(s) required:</u> 5516.12 Dome Port
50 mm Sony f/2.8 Macro	The magnifying effect of a flat port is good for macro photography. The front of the port is 67mm threaded. AF only. <u>Product(s) required:</u> 5516.45 Flat Port 5516.65 Extension	Larger radius dome is best for split shots (half-in, half-out of the water). AF only. <u>Product(s) required:</u> 5510.45 Dome 5516.65 Extension 5516.80 Adapter	Manual focus with optional focus gear. <u>Product(s) required:</u> 5516.15 Dome Port 5516.65 Extension <u>Optional accessories:</u> 5509.28 Focus Gear
50 mm Zeiss Touit f/2.8	AF only. <u>Product(s) required:</u> 5516.45 Flat Port 5516.65 Extension		
55-210 mm Sony f/4.5-6.3 OSS E SEL55210	Lens not recommended for use underwater due to range.		
60 mm Canon f/2.8 Macro + Metabones EF to E Mount Adapter <i>Tripod foot must be removed from Metabones adapter.</i>	AF only. <u>Product(s) required:</u> 5516.50 Flat Port 5516.65 Extension		
90 mm Sony f/2.8 G OSS Macro	AF only. <u>Product(s) required:</u> 5516.50 Flat Port 5516.70 Extension		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
100 mm Canon f/2.8L EF IS USM Macro + Metabones EF to E Mount Adapter <i>Tripod foot must be removed from Metabones adapter.</i>	AF only. <hr/> Product(s) required: 5516.50 Flat Port 5516.65 Extension 5516.70 Extension		