



WIDE ANGLE CONVERSION PORT WACP-C FOR FULL FRAME 28MM EQUIVALENT LENS TO EXTREME SHARP 130°

| | CAMERA LENS | GEAR | EXTENSION RING/ PORT ADAPTOR | PORT | OPTICAL PERFORMANCE |
|---|--|--|--|--|--|
| N120 CINEMA SYSTEM (RED, CANON, PANASONIC, Z-CAM, BLACKMAGIC) | STANDARD ZOOM | | APSC | | |
| | Canon EF-S 18-55mm f/3.5-5.6 IS STM | 16330 RC1855STM Gear Set | 21325 N120 to N100 25mm Port Adaptor | 85205 WACP - C | Lens FOV 71-29° Converted FOV 123-50° Zoom Range 20-55mm |
| | Sigma 18-35mm F1.8 DC HSM A | 16326 RSC1835F1.8 Gear Set | 21140 + 21325 N120 Extension Ring 40 with Lock + N120 to N100 25mm Port Adaptor | 85205 WACP - C | Lens FOV 71-46° Converted FOV 123-79.5° Zoom Range 20-35mm |
| | STANDARD ZOOM | | FULL FRAME | | |
| | Canon EF 28-80mm f/3.5-5.6 V USM | 16344 C2880VUSM Gear Set | 21325 N120 to N100 25mm Port Adaptor | 85205 WACP - C | On APS-C Sensor Lens FOV 52-22° Converted FOV 90-38° |
| | Canon EF 28-70mm f/3.5-4.5 II <i>* This lens is not supported by R5C camera in video mode</i> | 16334 RC2870II Gear Set | 21325 N120 to N100 25mm Port Adaptor | 85205 WACP - C | On APS-C Sensor Lens FOV 52-22° Converted FOV 90-38° On Full Frame Sensor Lens FOV 75-34° Converted FOV 130-59° |
| N120 NIKON F-MOUNT | STANDARD ZOOM | | DX | | |
| | Nikon AF-P DX NIKKOR 18-55mm f/3.5-5.6G | 19164 N1855AFP-Z | 21335 N120 to N100 35mm Port Adaptor | 85205 WACP - C | Lens FOV 76-29° Converted FOV 130-50° |
| | Nikon AF-P DX NIKKOR 18-55mm f/3.5-5.6G VR | 19164 N1855AFP-Z | 21335 N120 to N100 35mm Port Adaptor | 85205 WACP - C | Lens FOV 76-29° Converted FOV 130-50° |
| | Nikon AF-S DX Micro NIKKOR 18-55mm f/3.5-5.6G VR II | 19144 N1855VRII-Z | 21335 N120 to N100 35mm Port Adaptor | 85205 WACP - C | Lens FOV 76-29° Converted FOV 130-50° |
| | STANDARD ZOOM | | FX | | |
| | Nikon AF-S Nikkor 28mm f/1.8 G | | 21320 N120 to N100 20mm Port Adaptor | 85205 WACP - C | Lens FOV 75° Converted FOV 130° |
| Nikon AF Nikkor 28-70mm f/3.5-4.5D | 19148 N2870f3.5D-Z | 21335 N120 to N100 35mm Port Adaptor | 85205 WACP - C | Lens FOV 68-34° Converted FOV 117-59° Zoom Range 32-70mm | |
| N120 NIKON Z-MOUNT | STANDARD ZOOM | | FX | | |
| | Nikkor Z 24-70mm f/4 S Lens | 19154 NZ2470-Z | 21320 N120 to N100 20mm Port Adaptor | 85205 WACP - C | Lens FOV 75-70° Converted FOV 130-121° Zoom Range 28-32mm |
| | Sony SEL2870 FE 28-70mm F3.5-5.6 OSS with Megadap ETZ 21 Adaptor | 19158 NE2870-Z | 21315 N120 to N100 15mm Port Adaptor | 85205 WACP - C | Lens FOV 75-34° Converted FOV 130-59° |

** slight vignetting when focus distance from port to subject is less than 10cm at 28mm*



WIDE ANGLE CONVERSION PORT WACP-C FOR FULL FRAME 28MM EQUIVALENT LENS TO EXTREME SHARP 130°

| | CAMERA LENS | GEAR | EXTENSION RING/ PORT ADAPTOR | PORT | OPTICAL PERFORMANCE | |
|--------------------------|-----------------------------|--|-----------------------------------|---|---|---|
| N120 CANON EF-MOUNT | STANDARD ZOOM APSC | Canon EF-S 18-55mm f/3.5-5.6 IS STM | 19547 C1855ISSTM-Z | 21325 N120 to N100 25mm Port Adaptor | 85205 WACP - C | Lens FOV 75-27.5° Converted FOV 130-46° |
| | | Sigma 18-35mm F1.8 DC HSM A | 19552 SC1835f.18-Z | 21140 + 21325 N120 Extension Ring 40 with Lock + N120 to N100 25mm Port Adaptor | 85205 WACP - C | Lens FOV 76.5-44° Converted FOV 132-76° |
| | STANDARD ZOOM FULL FRAME | Canon EF 28-80mm f/3.5-5.6 V USM | 19559 C2880f3.5V-Z | 21325 N120 to N100 25mm Port Adaptor | 85205 WACP - C | Lens FOV 75-31° Converted FOV 130-54° |
| | | Canon EF 28-70mm f/3.5-4.5 II | 19557 C2870f3.5II-Z | 21325 N120 to N100 25mm Port Adaptor | 85205 WACP - C | Lens FOV 72-34° Converted FOV 130-59° <i>* slight vignetting when focus distance from port to subject is less than 10cm at 28mm</i> |
| | | Canon EF 28-80mm f/3.5-5.6 II | 19558 C2880f3.5II-Z | 21325 N120 to N100 25mm Port Adaptor | 85205 WACP - C | Lens FOV 75-30° Converted FOV 130-54° <i>* slight vignetting when focus distance from port to subject is less than 10cm at 28mm</i> |
| | N120 PANASONIC L-MOUNT | STANDARD ZOOM FULL FRAME | Panasonic Lumix S 24-105mm f/4 | 19721 PS24105-Z | 21335 N120 to N100 35mm Port Adaptor | 85205 WACP - C |
| CANON EF-MOUNT | | Canon EF 28-70mm f/3.5-4.5 II with Sigma Mount Converter MC-21 | 19557 C2870f3.5II-Z | 21325 N120 to N100 25mm Port Adaptor | 85205 WACP - C | Lens FOV 72-34° Converted FOV 130-59° |
| N100 FUJIFILM X-MOUNT | STANDARD ZOOM APSC | Fujifilm XF 18-55mm f/2.8-4 R LM OIS | 36474 X1855-Z3 | 37401 N100 Extension Ring 30 | 85205 WACP-C | Lens FOV 75-52° Converted FOV 130-90° Zoom Range 18-30mm |
| N100 SONY E-MOUNT | STANDARD ZOOM FULL FRAME | Sony SEL28F20 FE 28mm f/2 | 37150 SE28-F | 37401 N100 Extension Ring 30 | 85205 WACP-C | Lens FOV 75° Converted FOV 130° |
| | | Sony SEL2860 FE 28-60mm F4-5.6 | 37163 SFE2860-Z | 37401 N100 Extension Ring 30 | 85205 WACP-C | Lens FOV 75-40° Converted FOV 130-69° |
| | | Sony SEL2870 FE 28-70mm F3.5-5.6 OSS | 37141 SE2870-Z | 37403 N100 Extension Ring 50 | 85205 WACP-C | Lens FOV 75-34° Converted FOV 130-59° |



WIDE ANGLE CONVERSION PORT WACP-C

FOR FULL FRAME 28MM EQUIVALENT LENS TO EXTREME SHARP 130°

| | CAMERA LENS | GEAR | EXTENSION RING/ PORT ADAPTOR | PORT | OPTICAL PERFORMANCE |
|--|--|---------------------------|--|------------------------|--|
| N100 CANON RF-MOUNT STANDARD ZOOM APSC | Canon RF-S 18-45mm f/4.5-6.3 IS STM | 19596 CRS1845-Z | 37402 N100 Extension Ring 40 | 85205 WACP-C | Lens FOV 74-34° Converted FOV 128-59° |

85205

N100 0.36x Wide Angle Conversion Port Compact (WACP-C)

Package includes :

WACP-C with integrated Float Collar
 Hard Lens Cap
 Rear Port Cap
 Spare O-ring 90141
 Lubricant
 Cleaning Cloth
 Carrying Bag

Specification :

| | |
|--------------------|--|
| Dimension(mm): | DIA 170 x L145 |
| Weight in Air | 2.24kg |
| Buoyancy in Water | negative 0.1kg |
| Body Construction | Hard-anodized aluminum alloy |
| Lens Construction | 6 Elements in 5 Groups |
| Lens Coating | Anti-reflection Coating on both sides |
| Lens Mount | N100 Port Mount |
| Depth Rating | 100m |
| Focal Distance | From front element of lens to infinity |
| Field of View (UW) | 130° (ref 28mm equiv.) |