



N100 PORT SYSTEM FOR NIKON Z-MOUNT CAMERA SYSTEM (DX & F-Mount Format Lens)

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO DX	NIKKOR Z MC 50mm f/2.8 Macro			37401 N100 Extension Ring 30	37601 N100 Flat Port 29	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 1.3X Working Distance 8-66mm
							81302 CMC - 2	Max. Magnification 1.2X Working Distance 4-120mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 1.3X Working Distance 8-66mm
							81302 CMC - 2	Max. Magnification 1.2X Working Distance 4-120mm
					83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV 31.5° Converted FOV 119°	
					37124 Flat port 66 with M77 Thread	SMC/CMC Option 1 - Bayonet Mount 83251 + 83214 M77 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 1.3X Working Distance 8-66mm
							81302 CMC - 2	Max. Magnification 1.2X Working Distance 4-120mm
						83251 M77 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV 31.5° Converted FOV 119°
STANDARD ZOOM DX	NIKKOR Z DX 16-50mm f/3.5-6.3 VR		37602 Z1650PZ-Z		37601 N100 Flat Port 29	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.9X Working Distance 45.5-75mm
							81302 CMC - 2	Max. Magnification 0.67X Working Distance 70-130mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 0.9X Working Distance 45.5-75mm
							81302 CMC - 2	Max. Magnification 0.67X Working Distance 70-130mm
					83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV 84-31.5° Converted FOV 130-49°	
						¹ 83201 WWL-1	Lens FOV 72-31.5° Converted FOV 125-55° Zoom Range 20-50mm	
						83202 WWL-1B	Lens FOV 72-31.5° Converted FOV 125-55° Zoom Range 20-50mm	
NIKON F-MOUNT	Nikon F-mount Lenses with Nikon Adaptor FTZ <i>* It is required to replace tripod socket cover of Nikon adaptor FTZ by #25220 Tripod socket replacement</i>		37305 N100 to N120 35.5mm Port Adaptor II		N120 Nikon F-Mount Port System			

¹ We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.
Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance